



## VLR® Vinyl Lifter

### Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)  
Date of issue: 02/01/2019 Revision date: 04/11/2022 Version: 2.0

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product name : VLR Vinyl Lifter  
Product code : 1025

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Vinyl Letter Remover  
Use advised against : None identified

##### 1.3. Details of the supplier of the safety data sheet

Albatross USA Inc.  
36-41 36th Street  
Long Island City, NY 11106  
Tel: 718-392-6272

##### 1.4. Emergency telephone number

Emergency number : Spill, leak, fire, exposure or accident – Call CHEMTREC – Day or Night  
1 800-424-9300 or 1 703-527-3887 (USA & Canada)  
01-800-681-9531 (Mexico)

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification

Flammable Liquid, Category 2  
Eye Damage/Irritation, Category 2A  
Specific Target Organ Toxicity (Single Toxicity), Category 3

##### 2.2. Label elements

###### Labelling

Hazard pictograms :  

Signal word : Warning

Hazard statements : Flammable liquid and vapor  
Causes serious eye irritation  
May cause drowsiness or dizziness

Precautionary statements : Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Ground/Bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/fume/gas/mist/ vapors/spray.  
Use only outdoors or in a well-ventilated area.  
Wash hands thoroughly after handling.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

## Vinyl Liftoff

### Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

and easy to do. Continue rinsing.  
If eye irritation persists: get medical advice/attention.  
If inhaled: Remove person to fresh air and keep comfortable for breathing.  
Call a poison center/doctor/.../if you feel unwell.  
In case of fire: Use water spray, alcohol resistant foam, carbon dioxide (CO<sub>2</sub>), dry extinguishing powder to extinguish.  
Store in a well-ventilated place. Keep cool. Keep container tightly closed.  
Store locked up.  
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

##### 2.3. Other hazards

Other hazards which do not result in classification : Exposure to the concentration higher than TLV may cause upper respiratory tract irritation; a headache; ocular nerve damage.

##### 2.4. Unknown acute toxicity

Not applicable

#### SECTION 3: Composition/information on ingredients

##### 3.1. Substances

Not applicable

##### 3.2. Mixture

Name	Product identifier	%
Acetic acid, methyl ester	(CAS No) 79-20-9	60 - 90
1,3-Dioxolane	(CAS No) 646-06-0	10 - 30

The specific chemical/component identities and/or the exact component percentages of this material may be withheld as trade secrets.  
This information is made available to health professionals, employees, and designated representatives in accordance with the applicable provisions of 29 CFR 1910.1200 (f)(1).  
Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, mutagen, and reproductive toxicant, respiratory tract and skin sensitizers in addition to oral/ inhalation acute toxicant in category 1 and 2). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents.

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

First-aid measures, general : Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Consult a physician.  
First-aid measures after skin contact : Wash skin with plenty of water. Seek medical advice if irritation persists.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention.  
First-aid measures after ingestion : If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting. Obtain emergency medical attention. Call a POISON CENTER or doctor/physician.

##### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after eye contact : Exposure to high concentration of vapors or direct contact with eyes causes serious eye irritation. Symptoms include stinging, watering, redness, and swelling.  
Symptoms/injuries after inhalation : Inhaling a high concentration of vapor may cause respiratory tract irritation, a headache and ocular nerve damage.

##### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

##### 5.1. Extinguishing media

#### SECTION 5: Firefighting measures

##### 5/1 Extinguishing media

Suitable extinguishing media : Water spray, alcohol resistant foam, carbon dioxide (CO<sub>2</sub>), dry extinguishing powder to extinguish.  
Unsuitable extinguishing media : Avoid using stream water on burning liquid as it may scatter the flame.

Vinyl Liftoff

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

<b>5.2. Special hazards arising from the substance or mixture</b>		
Fire hazard	:	Flammable liquid and vapor
Explosion hazard	:	In the event of fire or heat exposure, a pressure increase will occur that can result in container burst.
<b>5.3. Advice for firefighters</b>		
Firefighting instructions	:	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protective equipment for firefighters	:	Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	:	Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).

SECTION 6: Accidental release measures

<b>6.1. Personal precautions, protective equipment and emergency procedures</b>		
General measures	:	Stop leak if safe to do so. Remove ignition sources. Use special care on handling. Avoid source of ignition and heat. No open flames. No smoking. Danger of slipping by leaking/spilling product. Avoid contact with eyes. Avoid breathing mist, spray and vapors.
<b>6.1.1. For non-emergency personnel</b>		
Emergency procedures	:	Evacuate unnecessary personnel.
<b>6.1.2. For emergency responders</b>		
Protective equipment	:	Equip cleanup crew with proper protection.
Emergency procedures	:	Evacuate unnecessary personnel. Depending on the condition, adequate ventilation might be required. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in confined and low areas.
<b>6.2. Environmental precautions</b>		
Prevent entry to sewers and public waters.	:	Notify authorities if liquid enters sewers or public waters.
<b>6.3. Methods and material for containment and cleaning up</b>		
Methods for cleaning up	:	Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect all waste in suitable and labelled containers and dispose according to local legislation. Store away from other materials. Ensure all national/local regulations are observed.
<b>6.4. Reference to other sections</b>		
Refer to section 8 and 13.	:	

SECTION 7: Handling and storage

<b>7.1. Precautions for safe handling</b>		
Additional hazards when processed	:	Handle empty containers with care because residual vapors may beflammable.
Precautions for safe handling	:	Read label before use. Obtain special instructions before use. Obtain special instructions before use. No smoking, open flames or sources of ignition in handling and storage area. Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	:	Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
<b>7.2. Conditions for safe storage, including any incompatibilities</b>		
Technical measures	:	Contains even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar opertaions on or near empty contains.
Storage conditions	:	Keep only in the original container in a cool well-ventilated place. Keep container closed when not in use. Keep away from incompatible materials. Keep away from sources of ignition, heat and open flames.
Incompatible materials	:	Oxidizing agents. Strong acids. Bases.
Incompatible condition	:	Avoid sources of ignition, heat and open flames.
<b>7.3. Specific end use(s)</b>		
Apart from the uses mentioned in section 1.2 no other specific uses are stipulated	:	


Vinyl Liftoff

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 8: Exposure controls/personal protection

<b>8.1. Control parameters</b>		
<b>Methyl acetate (79-20-9)</b>		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	Remark	Eye and upper respiratory tract irritation; headache; ocular nerve damage
OSHA	PELs TWA (mg/m3)	610 mg/m3
OSHA	PELs TWA (ppm)	200 ppm
OSHA	PELs STEL (mg/m3)	760 mg/m3
OSHA	PELs TWA (ppm)	250 ppm
<b>1,3-Dioxolane (646-06-0)</b>		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark	Hematologic effects- Critical effects

<b>8.2. Exposure controls</b>	
Appropriate engineering controls	: Ensure good ventilation of the work station. Eyewash fountains are suggested near any potential exposure. Use process enclosure, local exhaust ventilation or other engineering controls to keep workers exposure to the airborne contaminant below ant recommended limits.
Personal protective equipment	: Handle in accordance with good industrial hygiene and safety practices. Avoid all unnecessary exposure. For certain operations, additional Personal Protection Equipment (PPE) may be required.  Protective goggles. Gloves. Insufficient ventilation: wear respiratory protection.  
Hand protection	: In case of repeated or prolonged contact wear gloves.
Eye protection	: Wear goggles if splashing or spraying is anticipated.
Skin and body protection	: In case of repeated or prolonged exposure : Personal protective clothing should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

<b>9.1. Information on basic physical and chemical properties</b>	
Physical state	: Liquid
Appearance	: Clear
Color	: Colorless
Odor	: Solvent odor
Odor threshold	: No data available
pH	: Notapplicable
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 130 °F (55 °C) estimated
Flash point	: > 9 °F (-13 °C) estimated
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor pressure	: 22.83 kPa (at 20 °C) estimated

Vinyl Liftoff
Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Table with 2 columns: Property, Value. Rows include Relative vapor density at 20 °C, Relative density, Solubility, Log Pow, Log Kow, Viscosity, kinematic, Viscosity, Explosive properties, Oxidising properties, Explosive limits.

9.2. Other information
No additional information available

SECTION 10: Stability and reactivity

- 10.1. Reactivity
No additional information available
- 10.2. Chemical stability
The product is stable at normal handling and storage condition
- 10.3. Possibility of hazardous reactions
Under normal condition of use and storage, hazardous polymerization will not occur.
- 10.4. Conditions to avoid
Exposure to high temperature may produce hazardous decomposition material.
- 10.5. Incompatible materials
Strong oxidizing agents.
- 10.6. Hazardous decomposition products
Thermal decomposition products: Carbon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Table with 2 columns: Test, Result. Rows include Acetic acid, methyl ester (79-20-9), LD50 oral rat, LD50 dermal rabbit, LC50 inhalation rabbit (mg/l).

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified
(Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified
(No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC, NTP or OSHA)

Reproductive toxicity : Not classified
(Based on available data, the classification criteria are not met)

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness

Vinyl Liftoff
Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Specific target organ toxicity (repeated exposure) : Not classified
(Based on available data, the classification criteria are not met)

Aspiration hazard : Not classified
(Based on available data, the classification criteria are not met)

SECTION 12: Ecological information

12.1. Toxicity
Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

12.2. Persistence and degradability
No additional information available

12.3. Bioaccumulative potential
No additional information available

12.4. Mobility in soil
No additional information available

12.5. Other adverse effects
Effect on ozone layer : No additional information available
Effect on the global warming : No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to comply with applicable local, national and international regulations.
Waste treatment methods : Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

Domestic Ground Shipping (within the contiguous United States: \*Limited Quantity Exemption: This product, as packaged in 6 oz. containers, meets the exemption requirements of section 173.150 (49 CFR 173) as a limited quantity for ground shipments within the United States. Limited quantities require the limited quantity diamond mark on all outer cartons.

AIR TRANSPORT: We do NOT recommend this product to be shipped via air. It would need to be repacked by an authorized packing company and the DG would have to be completed by a licensed hazardous material shipping company.

Vinyl Liftoff
Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Table with 2 columns: Property and Value. Rows include Transport document description, UN-No.(DOT), Proper Shipping Name (DOT), Transport hazard class(es) (DOT), and Hazard labels (DOT).



Table with 2 columns: Property and Value. Rows include DOT Symbols and Packing group (DOT).

Table with 2 columns: Property and Value. Rows include DOT Special Provisions (49 CFR 172.102), DOT Packaging Exceptions (49 CFR 173.xxx), DOT Packaging Non Bulk (49 CFR 173.xxx), DOT Packaging Bulk (49 CFR 173.xxx), DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27), DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75), and DOT Vessel Stowage Location.

Additional information

Table with 2 columns: Property and Value. Rows include Transport by sea (IMDG) and Air transport (IATA/ ICAO).

SECTION 15: Regulatory information

Vinyl Liftoff
Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - NOTE: This product has NOT evaluated against the latest requirements of the California Proposition 65 to meet the safe harbor warning requirements introduced by The office of Environmental Health Hazards Assessment (OEHHA), during its OSHA hazards classification evaluation.

Methyl acetate (79-20-9)

Massachusetts RTK
Pennsylvania Worker and Community RTK

1,3-Dioxolane (646-06-0)

Massachusetts RTK
New Jersey Worker and Community RTK
Pennsylvania Worker and Community RTK

SECTION 16: Other Information

Table with 2 columns: Property and Value. Rows include Indication of changes and Revision date.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product