



Safety Data Sheet

1175 Dri Web Pallet Adhesive

1. Product Identification

Product Identifier: 1175 DRI-WEB PALLET ADHESIVE
Recommended Use: Adhesive
Manufacturer/Importer/Distributor Information: ALBATROSS USA INC
36-41 36TH STCUET
LONG ISLAND CITY, NY 11106 US 718-392-6272

Emergency Telephone: Spill, leak, fire, exposure or accident - Call CHEMTREC - Day or Night (USA & Canada) 1-800-434-9300 or 1-703-527-3887 (Mexico) +01-800-681-9531 (Australia) + (61)-290-372-994 (Belgium) + (32)-280-83237 (New Zealand) + (64)980-10034 (Netherlands) + (31)-858-880-596

2. Hazard(s) Identification

Classification
Flammable Aerosol, category 1
Aspiration Hazard, category 1
Eye Irritation, category 2A
STOT, single exposure, category 3, NE
Reproductive toxicity, category 2

Label elements

HAZARD PICTOGRAMS



SIGNAL WORD
Danger

GHS HAZARD STATEMENTS

H222 Extremely flammable aerosol.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.

GHS PRECAUTIONARY STATEMENTS

Prevention
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.

12642

P251 Do not pierce or burn, even after use.
P261 Avoid breathing dust, fumes, gas, mist, vapours, or spray.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear eye protection, face protection, protective gloves, and protective clothing

Response

P301+P310+P331 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice/attention.

Storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other Information

None

3. Composition/Information on Ingredients

Mixtures

Chemical Identity

Chemical Identity	CAS Number	Content In Percent (%)
Naphtha, (Petroleum), Hydrotreated Light	64742-49-0	10-25
Acetone	67-64-1	10-25
Dimethyl Ether	115-10-6	10-25
Propane	74-98-6	2.5-10
Butane	106-97-8	2.5-10
Methyl Acetate	79-20-9	2.5-10
n-Pentane	109-66-0	0.1-1.0
n-Hexane	110-54-3	0.1-1.0
Methanol	67-56-1	0.1-1.0

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition Comments: Other components are not hazardous or are below required disclosure limits.
The exact concentration has been withheld as a trade secret.

4. First-aid Measures

SKIN CONTACT: Remove contaminated clothing and wash the skin thoroughly with soap and water after work.

EYE CONTACT: Rinse immediately with plenty of water. Flush eyes with plenty of water for 15 minutes, while holding the eyelids apart. Check victim for contact lenses and remove if present. Get medical attention if irritation persists.

INHALATION: Move to fresh air. Remove victim to fresh air. If breathing is difficult, oxygen should be administered by qualified personnel. Get medical attention if you feel unwell.

INGESTION: Keep the victim calm and warm. Do NOT induce vomiting. If conscious, rinse mouth with water. Never give anything by mouth to an unconscious or convulsing person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration into the lungs. Get immediate medical attention.

IMPORTANT SYMPTOMS: Inhalation may cause drowsiness or dizziness. Aspiration hazard: Harmful or fatal if swallowed. May cause severe eye irritation.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED: Get medical attention if symptoms occur. Immediate medical attention is required for ingestion.

5. Fire-fighting Measures

EXTINGUISHING MEDIA: Use fire-extinguishing media appropriate for surrounding materials.

UNUSABLE EXTINGUISHING MEDIA: Do not use water jet as an extinguisher, as this will spread the fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Extremely flammable aerosol. Contents under pressure. Keep away from ignition sources and open flames. Prolonged exposure to temperatures above 120 °F may cause cans to burst. Vapors may travel considerable distance to a source of ignition and flash back. Combustion may produce carbon dioxide and carbon monoxide.

SPECIAL FIREFIGHTING PROCEDURES: No data available

6. Accidental Release Measures

PERSONAL PRECAUTIONS : Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Leaking cans should be placed in a plastic bag or open pail away from ignition sources until the pressure has dissipated. Collect liquid spill with an inert absorbent material and place into a suitable container for disposal.

ENVIRONMENTAL PRECAUTIONS: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. Environmental manager must be informed of all major spillages.

7. Handling and Storage

HANDLING: Keep away from sources of ignition - No smoking. Keep away from open flames, hot surfaces and sources of ignition. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

SAFE HANDLING ADVICE: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

STORAGE: Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

NFPA 308: Aerosol Level 2

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

Chemical Name	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING
Naphtha. (Petroleum). Hydro-treated Light	N.E.	N.E.	100 ppm	N.E.
Acetone	250 ppm	500 ppm	1000 ppm	N.E.
Dimethyl Ether	N.E.	N.E.	N.E.	N.E.
Propane	N.E.	N.E.	1000 ppm	N.E.
Butane	N.E.	1000 ppm	N.E.	N.E.
Methyl Acetate	200 ppm	250 ppm	200 ppm	N.E.
n-Pentane	1000 ppm	N.E.	1000 ppm	N.E.
n-Hexane	50 ppm	N.E.	500 ppm	N.E.
Methanol	200 ppm	250 ppm	200 ppm	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

ENGINEERING CONTROLS: No data available

Personal Protection

EYE/FACE PROTECTION: Wear goggles/face shield. Chemical safety goggles should be worn where contact is possible.

SKIN PROTECTION: No data available

RESPIRATORY / PROTECTION: Seek advice from local supervisor. In case of inadequate ventilation use suitable respirator.

HYGIENIC PRACTICES: When using do not smoke. Observe good industrial hygiene practices.

9. Physical and Chemical Properties

Appearance:

Physical State:

Form:

Color:

Odor:

Odor Threshold:

pH:

Freeze Point, °C:

Boiling Point, °C:

Flash Point, °C:

Flammability (solid, gas):

Evaporation Rate:

Combustibility:

Explosive Limits, %:

Vapor Pressure @20°C, PSI:

Vapor Density:

Relative Density:

Solubility in Water:

Partition Coefficient, n-octanol/water:

Auto-Ignition Temperature, °C:

Decomposition temperature, °C:

Kinematic Viscosity:

10. Stability and Reactivity

REACTIVITY: Not reactive under normal conditions of use.

STABILITY: Material is stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS: No data available

CONDITIONS TO AVOID: Keep away from heat, sparks, flames, and other sources of ignition. Do not puncture or incinerate containers. Dropping containers may cause bursting.

INCOMPATIBILITY: No data available

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion may produce carbon dioxide and carbon monoxide.

11. Toxicological Information

Information on Likely Routes of Exposure

SKIN CONTACT EFFECTS: May cause irritation on prolonged or repeated contact.

EYE CONTACT EFFECTS: Contact may cause severe irritation with redness, tearing and pain.

INHALATION EFFECTS: May cause central nervous system effects with drowsiness and dizziness.

INGESTION EFFECTS: Aspiration into the lungs during ingestion or vomiting may cause serious lung damage which may be fatal.

Carcinogenicity: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible, or confirmed human carcinogen by IARC, ACGIH, NTP or OSHA.

The following values are calculated based on chapter 3.1 of the GHS document. The product itself has not been tested.

ATE ORAL 9,532 mg/kg

ATE DERMAL 6,913 mg/kg

ATE INHALATION Not classified for acute toxicity based on available data.

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
64742-49-0	Naphtha, (Petroleum), Hydrotreated Light	5,000 mg/kg	3,750 mg/kg	100 mg/l
67-64-1	Acetone	5,800 mg/kg	7,426 mg/kg	50.1 mg/l
115-10-6	Dimethyl Ether	5,000 mg/kg	5,000 mg/kg	100 mg/kg
74-98-6	Propane	5,000 mg/kg	5,000 mg/kg	100 mg/l
106-97-8	Butane	5000 mg/kg	5000 mg/kg	658 mg/L Rat
79-20-9	Methyl Acetate	6,482 mg/kg	2,000 mg/kg	49.0 mg/L Rat
109-66-0	n-Pentane	2,000 mg/kg	5,000 mg/kg	364 mg/L Rat
110-54-3	n-Hexane	2,000 mg/kg	2,000 mg/kg	31.86 mg/l
67-56-1	Methanol	100 mg/kg	500 mg/kg	3 mg/l

N.I. = No Information

Skin Corrosion & Irritation:

Product: No data available

Serious Eye Damage & Irritation:

Product: No data available

Components:

Acetone 67-64-1 Causes serious eye irritation.
Methyl Acetate 79-20-9 Causes serious eye irritation.

Respiratory or Skin Sensitization:

Product: No data available

STOT-Single Exposure:

Product: No data available

Components:

109-66-0 May cause drowsiness or dizziness.
110-54-3 May cause drowsiness or dizziness.
67-64-1 May cause drowsiness or dizziness.
79-20-9 May cause drowsiness or dizziness.
Methyl Acetate

STOT-Repeated Exposure:

Product: No data available

Aspiration Hazard:

Product: No data available

Components:

Naphtha, (Petroleum), Hydrotreated Light 64742-49-0 May be fatal if swallowed and enters airways.
n-Pentane 109-66-0 May be fatal if swallowed and enters airways.
n-Hexane 110-54-3 May be fatal if swallowed and enters airways.

Carcinogenicity:

Product: No data available

Reproductive Toxicity:

Product: No data available

Components:

n-Hexane 110-54-3 Suspected of damaging fertility or the unborn child.

Germ Cell Mutagenicity:

Product: No data available

12. Ecological Information

ECOLOGICAL INFORMATION: No data available

PERSISTENCE: No data available

BIOACCUMULATE: No data available

MOBILITY IN SOIL: No data available

OTHER ECOLOGICAL: No data available

13. Disposal Information

DISPOSAL INFORMATION: Consult with your local, regional and federal agencies for information on proper disposal.

CONTAMINATED PACKAGING : Consult with your local, regional and federal agencies for information on proper disposal.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No data available

DOT

UN Number:

UN1950

Proper Shipping Name:

AEROSOLS, FLAMMABLE

Technical Name:

N/A

Hazard Class(es)

2.1

Class:

N/A

Subsidiary Risk

N/A

Packing Group:

N/A

IATA

UN Number:
Technical Name:
Hazard Class(es)
Class:
Subsidiary Risk:
Packing Group:

UN1950
AEROSOLS, FLAMMABLE
N/A
2.1
N/A
N/A

IMDG

UN Number:
Proper Shipping Name:
Technical Name:
Hazard Class(es)
Class:
Subsidiary Risk:
Packing Group:

UN1950
AEROSOLS, FLAMMABLE
N/A
2.1
N/A
N/A

Further Information

This document has been prepared using data from sources considered to be technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use are beyond the manufacturer's and seller's control. Purchaser and user are responsible for determining the suitability of the product for a particular purpose, adopting precautions for the protection of property and persons, and compliance with all Federal, State, Provincial, and Local laws.

The classification shown in this section may be eligible for use of an exception, such as 'Limited Quantity', per the dangerous goods regulations. The shipper of this product should consult the applicable mode's regulation for the UN number displayed above to determine if any exceptions are available and may be utilized, at the shipper's discretion.

15. Regulatory Information

CHEMICAL INVENTORY STATUS:

TSCA

On or in compliance with the inventory

DSL

All ingredients in this product are listed on the DSL or are exempt.

CALIFORNIA PROPOSITION 65 CARCINOGENS AND REPRODUCTIVE TOXINS:



Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

Chemical Name

n-Hexane
Methanol

CAS-No.

110-54-3
67-56-1

16. Other Information

Revision Date:

January 11, 2024

Datasheet produced by:

Regulatory Department

Legend

N/A - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information
TLV - Threshold Limit Values (TLVs®), as established by the American Conference of Governmental Industrial Hygienists (ACGIH®)
PEL - Permissible Exposure Limit, as established by the U.S. Occupational Safety and Health Administration (OSHA), as amended
TSCA - U.S. Toxic Substance Control Act
DSL - Canada Environmental Protection Act: Domestic Substance List

This information is being provided in accordance with the Occupational Safety and Health Administration (OSHA) regulation (29 CFR 1910.1200). The information supplied is designed for workplaces where the product use and frequency of exposure exceeds that established for the labeled consumer use.