



Epson SureColor F2260 DTG / DTF

- Direct-to-garment (DTG) and direct-to-film DTFilm printer
- New UltraChrome® DG2 ink for improved imaging on fabric and film
- Pouch-based ink supply for reduced production cost with less waste
- Latest Epson high-performance PrecisionCore MicroTFP printhead
- Efficient operation with auto height adjustment, frame and frame-less loading
- Quiet fan-less operation with self-cleaning printhead and capping system
- Supplied with upgraded Epson Garment Creator 2 application software
- Garments produced with this printer are suitable for use by all ages
- Improved ergonomics for easier installation and more efficient operation
- Comprehensive 'heads-and-all' warranty with service cover extendable up to five years and supported by Epson Cloud Solution PORT¹

Epson SureColor Fabric Range

SC-F2260 Desktop DTG/DTF Printer

Product Specifications

PRINTING TECHNOLOGY

Printhead	Epson 1.33" PrecisionCore® MicroTFP™
Print Modes	Uni & Bi-directional
Configuration	400 Nozzles x 8 lines
Maximum Resolution	1200 x 1200 dpi
Minimum Droplet Size	12.8 pl

INK SYSTEM

Ink Type	Epson UltraChrome® DG2
Standard Configuration	CYMK + Dual White + Maint Liquid
Loading	800 ml x 7 pouches, front tray system

PERFORMANCE²

Standard Configuration	Clr + Wht: 89s Fast / 142s Prodn / 321s Quality Wht Only: 52s Fast / 86s Prodn / 213s Quality Clr Only: 28s Fast / 43s Prodn / 128s Quality)
------------------------	--

MEDIA SUPPORT³

DTFilm Production	Various film & power combinations
DTG Production	Cotton, polyester and mixed fibre garments
Max Thickness / Weight	27 mm / 1.5 kg per garment
Max Print Area	Large Platen: 406 x 508 mm Medium & Grooved Platen: 335 x 406 mm

OPERATION

Control Panel	4.3" Colour touch LCD with USB print support ⁴
Utility Software	Epson Edge Dashboard, communications driver, s/w & f/w updater, EpsonNet set-up, config & print
Application Software	Epson Garment Creator 2 & Cloud Solution PORT
Interface	High Speed USB 2.0 and Ethernet 1000 Base-T
Memory	1GB

ENVIRONMENTAL

Operational Temp	10-35°C
Operational Humidity	20 to 80% (no condensation)
Power Supply	AC 240 V 1.6 A, 50 Hz - 60 Hz
Power Consumption	46 W Operating / 30 W Standby / 7 W Sleep
Operating Noise	37 dB

PHYSICAL

Printer (without ink)	981 mm x 499 mm x 1361 mm (WxHxD), 95 kg
Shipping Carton (Main Unit)	1434 mm x 897 mm x 1209 mm (WxHxD), 148 kg

WHAT'S IN THE BOX⁵

Printer, power cord, 1 x set 800 ml pouches, 20 litre pre-treat solution, medium hanger platen and grip pad, waste tank, maintenance kit and head cleaning set, set up guide. All software delivered via web download. On-line manual with help. On-line PORT service.

CONFIGURATION OPTIONS¹

SCF2260W1Y	Printer with 1Yr On-Site Wty
SCF2260W3Y	Printer with 1Yr On-Site Wty + 2Yr CoverPlus
SCF2260W5Y	Printer with 1 Yr On-Site Wty + 4Yr CoverPlus

OPTIONAL ACCESSORIES

C12C938911	Large Hanger Platen
C12C938991	Grooved Platen (for shirts with buttons or a zipper)
C12C938931	Medium Hanger Platen
C12C939031	Small Hanger Platen
C12C933951	Extra Small Platen
C12C939051	Sleeve Platen

CONSUMABLES

C13T54R900	800 ml Cleaning Liquid
C13T54LB00	800 ml Maintenance Liquid
C13T54L100~400, A00	800 ml ink pouches (K/C/M/Y/W)
C13T43R100	20 L Cotton pre-treatment liquid (concentrate)
C13T43R200	18 L Polyester pre-treatment liquid
C13S400216	Head Cleaning Set kit
C13T736200	Maintenance Kit
C13S210118	Large Hanger Platen grip pad
C13S21011	